

Description

Exhaust Repair Paste has been developed for carrying out quick, simple and economical repairs to exhaust systems. The Exhaust Repair Paste does not contain asbestos or solvent, does not pollute the environment, is heat resistant and provides a gas-tight seal to small holes and cracks in exhaust systems.

Properties

- simple to use
- no dismantling or welding work necessary
- does not contain flammable solvents
- does not contain asbestos
- high gas tightness
- cost-effective repairs
- outstanding thermal resistance

legally binding.



Technical data

Form	pastelike, solid
pH value	~ 10
Odor	odourless
Density	~ 1,92 g/cm ³
Base	inorganic materials
Thermal stability	ca. 700 °C
Color / appearance	dark grey
Solubility	insoluble
Shelf life in original sealed container	24 months

Areas of application

Used for eliminating leaks and sealing small holes and cracks in exhaust systems.

Application

Thoroughly clean dirt and rust from the parts to be treated. Allow the engine to run until the exhaust system has heated up. Moisten the place to be repaired and the Exhaust Repair Paste and press paste into the damaged area. Smooth down the moistened paste. The paste is hardened by heat radiating from the exhaust system or from the engine idling.

Available pack sizes

200 g Tube plastic	2898
	GB-DK-FIN-N-S
200 g Tube plastic	3340
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not