

## NSB 40FT BLUE+



# The NSB BLUE+ Battery® delivers ultra fast recharge and exceptional PSoC cycling performance.

- Exceptional PSoC cyclic performance 2050 cycles @50% DoD
- Design life 12+ years at 20°C (68°F)
- Ultra fast recharge
- Shelf life of up to 24 months
- Lead carbon added to negative electrodes increases power and reduces sulfation
- High potential fuel savings when used with hybrid genset applications

- Operating temperature range -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability
- Advanced 3 stage terminal design to ensure leak-free operation - brass terminals provide maximum performance
- High modulus Polyphenylene Oxide (PPO) plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Non-halogenated thermally sealed plastic casing
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)



# NSB 40FT BLUE+

## Nominal Technical Specifications


### **Dimensions**

Height	208 mm	Width	97 mm
Length	250 mm	Weight	14 kg

### **Flectrical**

Terminal	Female M6 x 1.0	
Terminal torque	8.0 Nm (71 in-lbs)	
10 hr capacity to 1.80VPC @ 25°C (77°F)	37 Ah	
8 hr capacity to 1.75VPC @ 25°C (77°F)	37 Ah	
Float voltage @ 20/25°C (68/77°F)	2.28 / 2.27 VPC	
Impedance (1Khz)	3.9 m <b>Ω</b> @ 25°C (77°F)	
Conductance	1114S	
Short circuit current	1500 A	
Maximum charge current (A)	No Limit	
Operation temperature range	-40°C to +65°C	
Nominal voltage	12 V	

## Technical Drawing



All NorthStar batteries are compliant with: Telcordia SR4228, IEC 60896; Bellcore GR-63-Core, Issue 1; British, German, and Russian telecom standards; UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.