

Fast Charge Jump Starter 360 & 13000mAh Power Bank



<p>UP TO 6.0L Petrol</p> <p>Engine size</p>	<p>UP TO 3.0L Diesel</p> <p>Engine size</p>	<p> Fast Start <60 Seconds</p>	<p> USB Powerbank 1 x PD30 Type C 1 x QC3.0</p>	<p> LED Light</p>	<p> Storage Bag</p>
--	--	---------------------------------------	---	-----------------------	-------------------------

PD30W
RAPID TECHNOLOGY

FAST CHARGING

FAST RECHARGE



Motorcycle	Car	Van	4x4
------------	-----	-----	-----

- **A powerful, safe and compact Lithium jump starter**
That also provides power to electronic gadgets
- **Up to 30W PD Fast charge of phones and tablets**
Type-C USB fast charging
- **Compact design**
That easily fits into your glove box
- **Fast 1.5h recharge with 30W PD charger**
4.5h recharge with 5V 2A charger
- **Suitable for motorcycles, cars, 4x4s and vans**
With up to 6.0L petrol or 3.0L diesel engines
- **Safe connect system**
To protect the user, vehicle and jump starter
- **Intelligent clamps**
Safely manage power between the jump starter and the vehicle
- **Reverse polarity, over temperature protection and battery cell balancing**
- **LED Torch**
Also with SOS function
- **Supplied with Type-C to Type-C and Type-A to Type-C USB cables**

Specifications

Product Code	RPPL360
Internal Battery Voltage (nominal)	14.8V
USB Output	PD30 Type C: 5V 3A, 9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A QC3.0 USB: 5V 2.4A, 9V 2A, 12V 1.5A
Starting Current	300A
Peak Current	1500A
Max Cranking Time	3 secs
Battery Type	Lithium Cobalt LiCoO2
Battery Capacity	13,000mAh (48.1Wh)
Operating Temperature	-20C to 40C
Cable Clamp Opening	30mm
Weight	840g
Product Dimensions	171 x 88 x 33
Pack Dimensions	226 x 134 x 94
Case Quantity	4 x 1
Barcode	5055175250151

Ring Automotive Limited

Gelderd Road, Leeds, LS12 6NA United Kingdom
Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266
Email: autosales@ringautomotive.com . www.ringautomotive.com
 /ringautomotive

Authorised Representative:

OSRAM GmbH
Nonnendammallee 44, 13629 Berlin, Germany
Email: automotive-service@osram.com
www.osram.com