

SynPower™ FE 5W20 Synthetic Motor Oil

ersion: 6.0	Revision Date: 07	1.07.2020	Print Date: 16/09/2022
Conforms to EU Regulation 1907/2006/EC as amended SDSGHS_GB SECTION 1: Identification of the substance/mixture and of the company/undertaking			
1.1 Product identifier Trade name	: SynPowe Synthetic	™ FE 5W20 Motor Oil	
Product code	: 872555		
 1.2 Relevant identified u Recommended use 1.3 Details of the supplie sheet Ellis Enterprises B.V., an a 	: Engine, gear r of the safety data	& lubricating oil. 1.4 Emergency telep 00-800-825-8654 / 00 ⁻	
Wieldrechtseweg 39 3316 BG Dordrecht Netherlands +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person		Product Information +31 (0)78 654 3500 (ir contact your local CSF	the Netherlands), or
SDS@valvoline.com			

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210	Safety data sheet available on request.
EUH208	Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

dithiocarbamate complex. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. **Additional advice**

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 70,00 - < 80,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	457-320-2 01-0000019337-66-xxxx	Skin Irrit.2; H315 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 0,10 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air.
	2/20



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
	If unconscious, place in recovery advice. If symptoms persist, call a physici	
In case of skin contact	: First aid is not normally required. recommended that exposed areas with soap and water.	
In case of eye contact	: Flush eyes with water as a precau Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a	
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beve Never give anything by mouth to a If symptoms persist, call a physici	an unconscious person.
4.2 Most important symptoms ar	nd effects, both acute and delayed	
Symptoms	: No symptoms known or expected	
4.3 Indication of any immediate	medical attention and special treatm : No hazards which require special	
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use extinguishing measures that circumstances and the surroundin Water spray Foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	: High volume water jet	
5.2 Special hazards arising from	the substance or mixture	
Specific hazards during firefighting	: Do not allow run-off from fire fight courses.	ing to enter drains or water



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
Hazardous combustion products	: Nitrogen oxides (NOx) carbon dioxide and carbon monoxide	
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-contained b	reathing apparatus.
Specific extinguishing methods	: Product is compatible with standard fire-	fighting agents.
Further information	: Standard procedure for chemical fires.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Comply with all applicable federal, state, and local regulations.
6.2 Environmental precautions	
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for co	ntainment and cleaning up
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Do not breathe vapours/dust.
	Do not smoke.
	Container hazardous when empty.
	Smoking, eating and drinking should be prohibited in the



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0		Re	evision Date: 01.07.2020	Print Date: 16/09/2022
			application area. For personal protection see section 8. Dispose of rinse water in accordance with regulations.	h local and national
	Advice on protection against fire and explosion	:	Normal measures for preventive fire prote	ection.
	Hygiene measures	:	Wash hands before breaks and at the en	d of workday.
7.2	Conditions for safe storage,	inc	luding any incompatibilities	
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and place.	d well-ventilated
	Other data	:	No decomposition if stored and applied a	s directed.
7.3	Specific end use(s) Specific use(s)	:	No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum polysulphide long chain alkyl dithiocarbamate complex		TWA	10 mg/m3	SUPLR EXP

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection

: Not required under normal conditions of use. Wear splashproof safety goggles if material could be misted or splashed into eyes.



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
Hand protection		
Remarks	: Nitrile rubber butyl-rubber	
	The suitability for a specific workplace with the producers of the protective glo	
Skin and body protection	: Wear as appropriate: Impervious clothing Safety shoes Choose body protection according to t concentration of the dangerous substa	
Respiratory protection	: No personal respiratory protective equ required.	ipment normally

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -39 °C
Boiling point/boiling range	:	No data available
Flash point	:	202 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: ca. 0,853 g/cm3 (15,6 °C)	
Solubility(ies) Water solubility	: insoluble	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: ca. 45,1 mm2/s (40 °C)	
Oxidizing properties	: No data available	
9.2 Other information Self-ignition	: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Product will not undergo hazardous polymerization.	
---------------------	--	--

10.4 Conditions to avoid

Conditions to avoid : None known.



SynPower™ FE 5W20 Synthetic Motor Oil

ersion: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
0.5 Incompatible materials		
Materials to avoid	: Strong oxidizing agents Strong bases	
0.6 Hazardous decomposition	products	
Hazardous decomposition products	: No hazardous decomposition pr	oducts are known.
ECTION 11: Toxicological	information	
1.1 Information on toxicologic	cal effects	
Information on likely routes of exposure	of : Inhalation Skin contact Eye Contact Ingestion	
Acute toxicity		
Not classified based on avai	lable information.	
Components:		_ .
Acute oral toxicity	m), C20-50, Hydrotreated Neutral Oil- : LD50 (Rat): > 5.000 mg/kg	Based:
	. LD30 (Nat). > 3.000 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 5,58 mg/l	
	Exposure time: 4 h	
	Test atmosphere: dust/mist Assessment: Not classified as ac	rutely toxic by inhalation
	under GHS.	
	Remarks: No mortality observed	at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5.000 mg/kg	
	Remarks: No mortality observed	at this dose.
Components:		
	ZENEAMINE, N-PHENYL- W/ NONEN	IE (BRANCHED):
Acute oral toxicity	LD50 (Rat): > 5.000 mg/kg	at this data
	Remarks: No mortality observed	at this dose.
A quite democl texticity		



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

ш

Revision Date: 01.07.2020

Print Date: 16/09/2022

C14-16-18 Alkyl phenol:	
Acute oral toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by ingestion unde GHS.
Acute dermal toxicity	 LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose.

Components:

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Acute oral toxicity	: LD50 (Rat): > 2.000 mg/kg
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit Result: No skin irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit Result: Mild skin irritation Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431 Result: No skin irritation

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Species: Rabbit Result: Irritating to skin.

.

Serious eye damage/eye irritation

Not classified based on available information.

Product:



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

Result: Slight, transient irritation Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit Result: Slight, transient irritation Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit Result: Slight, transient irritation

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Species: Rabbit Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation.

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay Species: Mouse Assessment: The product is a skin sensitiser, sub-category 1B.

10 / 20



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
Test Type: Maximisation T Species: Guinea pig	IOCARBAMIDE METAL COMPLEX:	
Germ cell mutagenicity Not classified based on av Components:	vailable information.	
	ENZENEAMINE, N-PHENYL- W/ NONE	NE (BRANCHED)
Genotoxicity in vitro	: Test Type: Ames test Test species: Salmonella typhim Metabolic activation: with and wi Result: negative	nurium
C14-16-18 Alkyl phenol:		
Genotoxicity in vitro	: Test Type: Ames test Test species: Salmonella typhim Metabolic activation: with and wi Result: negative	
LONG CHAIN ALKYL TH	IOCARBAMIDE METAL COMPLEX:	
Genotoxicity in vitro	: Test Type: Ames test Test species: Salmonella typhim Metabolic activation: with and wi Result: negative	
Carcinogenicity Not classified based on av	vailable information.	
Components:		_

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity -	
Assessment	

Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

C14-16-18 Alkyl phenol:

Target Organs: Liver Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based: May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:	
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C	C20-50, Hydrotreated Neutral Oil-Based	
Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility	
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	



SynPower™ FE 5W20 Synthetic Motor Oil

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test Type: static test Test Type: static test Toxicity to fish (Chronic : NOELR: >= 1.000 mg/l toxicity) Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout) Toxicity to daphnia and other aquatic invertebrates : NOEL: 10 mg/l (Chronic toxicity) Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211 bis(nonylphenyl)amine Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances. Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l aquatic invertebrates : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l Exposure time: 72 h Test Type: static test Test Type: static test Test Type: static test Toxicity to algae : EC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 26 h Test substance: WAF </th <th>ion: 6.0</th> <th>Revision Date: 01.07.2020</th> <th>Print Date: 16/09/2022</th>	ion: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
toxicity)Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity): NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211bis(nonylphenyl)amine Toxicity to fish: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAFToxicity to algae: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l Exposure time: 72 h Test Type: static testC14-16-18 Alkyl phenol Toxicity to fish: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static testC14-16-18 Alkyl phenol Toxicity to daphnia and other aquatic invertebrates: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static testToxicity to daphnia and other aquatic invertebrates: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static testC14-16-18 Alkyl phenol Toxicity to daphnia and other aquatic invertebrates: LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAFToxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	Toxicity to algae	100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	
aquatic invertebrates (Chronic toxicity)Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211bis(nonylphenyl)amine Toxicity to fish:LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.Toxicity to daphnia and other aquatic invertebrates:EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test 		Exposure time: 14 d	ainbow trout)
Toxicity to fish: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAFToxicity to algae: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static testC14-16-18 Alkyl phenol Toxicity to fish: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static testToxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 96 h Test Type: static testToxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 96 h Test Type: static testToxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	aquatic invertebrates	Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF	1
Toxicity to fish: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h 	bis(nonylphenyl)amine		
aquatic invertebratesExposure time: 48 h Test Type: static test Test substance: WAFToxicity to algae: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static testC14-16-18 Alkyl phenol:Toxicity to fish:LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static testToxicity to daphnia and other aquatic invertebrates:EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test	Toxicity to fish	Exposure time: 96 h Test Type: static test Remarks: Information given is bas	
End point: Growth inhibition Exposure time: 72 h Test Type: static testC14-16-18 Alkyl phenolToxicity to fish:LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAFToxicity to daphnia and other aquatic invertebrates:EC50 (Daphnia magna (Water flea)): > 100 mg/l 		Exposure time: <mark>48 h</mark> Test Type: <mark>static test</mark>	a)): > 100 mg/l
 Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 	Toxicity to algae	End point: Growth inhibition Exposure time: 72 h	pitata (algae)): 600 mg/l
Toxicity to fish: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAFToxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	C14-16-18 Alkyl phenol		
aquatic invertebrates Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	Toxicity to fish	Exposure time: 96 h Test Type: static test	100 mg/l
Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l		Exposure time: <mark>48 h</mark> Test Type: <mark>static test</mark>	



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
	End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	
Molybdenum polysulphide lon	ng chain alkyl dithiocarbamate complex	
Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainboy Exposure time: 96 h Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 203	<i>w</i> trout)): 94,8 mg/l
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	50 mg/l
Toxicity to algae	: NOELR (Pseudokirchneriella subcap mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: Information given is based similar substances.	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR: 100 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211)

12.2 Persistence and degradability

Components: Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based Biodegradability : Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B bis(nonylphenyl)amine Biodegradability : Result: Not readily biodegradable. Biodegradability bis(nonylphenyl)amine Biodegradability : Result: Not readily biodegradable. Biodegradability 2



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
	Exposure time: 28 d Method: OECD Test Guideline 301B	
C14-16-18 Alkyl phenol		
Biodegradability	: Result: Readily biodegradable. Remarks: Expert judgement	
Molybdenum polysulphic	le long chain alkyl dithiocarbamate complex	
Biodegradability	: Result: Not readily biodegradable. Biodegradation: 23 % Exposure time: 28 d Method: OECD Test Guideline 301B Remarks: Information given is based similar substances.	on data obtained from

12.3 Bioaccumulative potential

Components:

bis(nonylphenyl)amine	
Partition coefficient: n- octanol/water	: log Pow: > 7,5
C14-16-18 Alkyl phenol	
Partition coefficient: n- octanol/water	: log Pow: > 7,2
	chain alkyl dithiocarbamate complex
Partition coefficient: n-	: log Pow: > 5,1
octanol/water	Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment	 This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or
	very persistent and very bioaccumulative (vPvB) at levels of
	0.1% or higher

12.6 Other adverse effects

Product:

Additional ecological	: No data available
information	



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

SECTION 13: Disposal considerations

13.1	Waste	treatment	methods
	114010		moundad

Product	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

15.	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation (EC) No 1005/2009 on substances that : Not applicable deplete the ozone layer				
	Regulation (EC) No 850/2004 on persistent organic pollutants			:	Not applicable
	REACH - List of substances s (Annex XIV)	subje	ect to authorisation	:	Not applicable
	REACH - Candidate List of Su Concern for Authorisation (Ar			:	Not applicable
	Regulation (EC) No 649/2012 of the European : Not applicable Parliament and the Council concerning the export and import of dangerous chemicals				
	REACH - Restrictions on the the market and use of certain preparations and articles (Anr	dan	igerous substances,	:	Not applicable
			Directive 96/82/EC doe	es n	ot apply
	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable				
	The components of this pro	duc	-		-
	DSL	:	All components of this	pro	duct are on the Canadian DSL
	AICS	:	On the inventory, or in	con	npliance with the inventory
	ENCS	:	On the inventory, or in	con	npliance with the inventory
	KECI	:	On the inventory, or in	con	npliance with the inventory



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0	Revision Date: 01.07.2020	Print Date: 16/09/2022
PICCS	: On the inventory, or in compliance	with the inventory
IECSC	: On the inventory, or in compliance	with the inventory
TCSI	: Not in compliance with the invento	ry
TSCA	: On TSCA Inventory	

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000242474

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H412	Harmful to aquatic life with long lasting effects.			
H413	May cause long lasting harmful effects to aquatic life.			
Other information	 The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500). 			



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report



SynPower™ FE 5W20 Synthetic Motor Oil

Version: 6.0

Revision Date: 01.07.2020

Print Date: 16/09/2022

DNEL : Derived No Effect Level. EINECS : European Inventory of Existing Commercial Chemical Substances. ELINCS : European List of Notified Chemical Substances PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits PNEC : Predicted No Effect Concentration R-phrase : Risk phrase REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals RID : Regulation Concerning the International Transport of Dangerous Goods by Rail S-phrase: Safety phrase WGK : German Water Hazard Class